Industrial Ultrasonic Cleaner

CE







Advantage

1.Wide range of cleaning fluids, including alcohol, water or other solvents

2.Supports 24H continuous operation

3.Super waterproof performance, more durable

4.Shell, liner and basket are made of corrosion-resistant 304 stainless steel.

5.Time setting from 1-99 mins

6.Adjustable ultrasonic power for some models

7.Built-in heating system up to 110°C

8.Equipped with a heating thermostat system

9.Can customer some configurations

10.Drainage system for added convenience

Specification

Model	UC-I25	UC-I40	UC-I60	UC-I90	UC-I100	UC-I125
Tank Capacity(L)	23	38	56	88	101	126
Tank Material	SUS304					
Transducer Qty(Pcs)	6	12	18	24	30	36
Ultrasonic Freq(KHz)	28 or 40					
Temperature Setting(℃)-Max	110℃					
Drain valve	Yes					
Time Setting(min)	1-99 mins					
Separated Ultrasonic Generator	No (All-in-one)		Yes			
Heating Power Supply	AC 220-240V, 50/60Hz				AC 380V, 50/60Hz	
Generator Power Supply	AC 220-240V, 50/60Hz					
Ultrasonic consump-tion(W)-Max	300	600	900	1200	1500	1800
Heating consump-tion(W)-Max	1500		3000		4500	
Chamber Size (W×D×H)(mm)	305x250x305	355x305x355	406x305x460	500x355x500	500x406x500	500x460x550
Sizes (W×D×H)(mm)	485x430x705	535x485x755	586x485x680	680x535x720	680x586x720	680x640x770
Shipping Size (W×D×H)(mm)	630x560x920	660x610x970	720x610x900	810x660x940	810x710x940	810x760x990

Specification

Model	UC-I150	UC-I170	UC-I190	UC-I210	UC-I230	UC-I250
Tank Capacity(L)	150	170	190	210	230	250
Tank Material	SUS304					
Transducer Qty(Pcs)	42	48	54	60	66	72
Ultrasonic Freq(KHz)	28 or 40					
Temperature Setting(℃)-Max	110℃					
Drain valve	Yes					
Time Setting(min)	1-99 mins					
Separated Ultrasonic Generator	Yes					
Heating Power Supply	AC 380V, 50/60Hz					
Generator Power Supply	AC 220-240V, 50/60Hz					
Ultrasonic consump-tion(W)-Max	Customized					
Heating consump-tion(W)-Max	Customized					
Chamber Size (W×D×H)(mm)	Customized					
Sizes (W×D×H)(mm)	Customized					
Shipping Size (W×D×H)(mm)	Customized					